

SELECTION & SPECIFICATION DATA

Generic Type	A fast dry acrylic enamel
Features	<ul style="list-style-type: none"> • Fast dry properties • Flat finish
Color	Grey
Finish	Flat
Dry Film Thickness	1 - 1.5 mils (25 - 38 microns) per coat
Solids Content	By Volume 30% +/- 2%
Theoretical Coverage Rate	481 ft ² /gal at 1.0 mils (11.8 m ² /l at 25 microns) 321 ft ² /gal at 1.5 mils (7.9 m ² /l at 38 microns) Allow for loss in mixing and application.
VOC Values	As Supplied : 5.1 lbs/gal (610 g/l) These are nominal values and may vary slightly with color.

SUBSTRATES & SURFACE PREPARATION

General | Surfaces should be free of dust, dirt, oils, moisture and other contaminants. This product should be applied over properly primed steel, galvanized and aluminum.

MIXING & THINNING

Mixing | Thoroughly mix to be assured that all settling has been eliminated and that a good homogeneous color exists.

Thinning | Thinner 10, as needed

APPLICATION EQUIPMENT GUIDELINES

Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

General | Conventional or Airless spray preferred. If it is necessary to apply by roller, consult your Carboline representative.

CURING SCHEDULE

Surface Temp.	Dry to Touch	Dry to Handle
77°F (25°C)	30 minutes	1 Hour

CLEANUP & SAFETY

Cleanup | Clean all equipment with Thinner 10.

Driquik Acrylic Enamel

PRODUCT DATA SHEET



CLEANUP & SAFETY

	Keep away from sparks or flame. Vapors may cause flash fire. Use with adequate ventilation. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator during applications unless air monitoring demonstrates vapor/mist levels are below applicable limits. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.
Safety	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling content may be harmful or fatal. Follow all precautions. See product MSDS for more detailed information. FOR PROFESSIONAL USE ONLY! WARNING! FLAMMABLE. HARMFUL IF INHALED. CAUSES IRRITATION

PACKAGING, HANDLING & STORAGE

Packaging	Hazard Class: Flammable Liquid UN No.: 1263
Shelf Life	1 year
Storage Temperature & Humidity	40°F (4°C) to 100°F (38°C)
Shipping Weight (Approximate)	9 lbs/gal (1.1 kg/l)
Flash Point (Setaflash)	55°F (13°C)

WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.